MI-WAVE®
Millimeter Wave Products Inc.

# 521E-6/387

**TEST DATA SHEET**

## Description

Mi-Wave's 521 series Fixed Attenuators

## Notes

S/N: VUDZQ3 WUDZRV

## Electrical Specifications

| | Minimal | Typical | Maximum |
|---|---|---|---|
| Frequency | 60 GHz | | 90 GHz |
| Attenuation @ 75 GHz | | 6 dB | |
| VSWR | | 1.15:1 | |
| Average Power Handling | | | 1 Watts |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |

## Physical Specifications

| | |
|---|---|
| Input and Output Ports | WR-12 Waveguide |
| Flange Type | UG-387/U Flange |
| Material Type | Aluminum |
| Finish | Gold Plated |
| Weight | 0.5 oz |
| | |
| | |
| | |

**Tested by:** Kim Madden

**Date:** 2022-12-13

Millimeter Wave Products Inc. • 2007 Gandy Blvd N., Suite 1310, St. Petersburg, FL 33702
**Phone:** (727) 563-0034 • **Fax:** (727) 563-0031 • **Email:** Sales@miwv.com

RoHS compliant

REACH COMPLIANCE