

Description

Mi-Wave's 511 series Programmable Rotary Vane Attenuators

Notes

Other Features: Mode Free Back-lit Display Fast Operation Interactive User menu Long MTBF

S/N: 1020

Electrical Specifications

	Minimal	Typical	Maximum
Frequency Range	220 GHz		325 GHz
Attenuation Range	0 dB		40 dB
Resolution (for 0-40 dB attenuation range)	0	0.01 dB steps	40 dB
Insertion Loss		7 dB	
VSWR		1.4:1	
Speed (attenuation change from 0-40 dB)		less than 2 seconds	
MTBF		>1000000 cycles	
Operating Voltage(100-240 Vac adapter is supplied)		24 Volts	
Programmable GPIB Address		up to 30	
Power Handling (CW)			0.05 Watts
Calibration	0	40	50
Calibration Accuracy 0 to 40 db		2%	
Calibration Accuracy 40 to 50 db (ref. only)		3%	
Calibration Accuracy 50 to 60 db (ref. only)		4%	

Physical Specifications

Input and Output Port	WR-03 Waveguide, UG-387/U Flange
Remote Control Interface	IEEE-488 and USB port
Manual Control Interface	4 LED Buttons
Weight	4-5 lbs

Tested by: Kim Madden

Date: 2021-03-11

